

PROJECTOR 100

CONSTRUCTION & ENVIRONMENT

Evacuation and material handling hoses



Applications

For spraying of wet mortar, mixed concrete, and other wet products.

Used as a service hose between pump and nozzle in transporting plaster, grout, and ready mixed concrete.

Advantages

- High working pressure.
- Light weight, flexible and easy to handle.
- Abrasion resistant tube.

Technical description

Inner tube: wear resistant NR, black, smooth.

Reinforcement: synthetic textile.

Cover: weather and wear resistant SBR, black, fabric impression.

Temperature range: - 30 °C to + 70 °C.

Electrical properties: conductive tube, $R < 2 \cdot 10^6 \Omega/m$.

Special properties: abrasion resistance of tube $< 70 \text{ mm}^3$ according to DIN 53 516.

Complementary information

13.3 m lengths available on request, min. order is three pieces and by multiple of three.

Other wall thickness and/or bursting pressure on request.

PROJECTOR 100

29/01/2008

ID	Wall thickness		OD		Working pressure	Bursting pressure	Bending radius	Weight	Length	Article number	Stock (■) or min. order
mm	mm		mm		bar	bar	mm	kg/m	m		m
25.0	7.0	+ 0/- 1	39.0	± 1.0	40	100	100	0.87	40	0061494	■
32.0	8.0	+ 0/- 1	48.0	± 1.0	40	100	150	1.24	40	0127153	400
35.0	6.5	+ 0/- 1	48.0	± 1.0	40	100	180	1.06	40	0061496	■
38.0	10.0	+ 0/- 1	58.0	± 1.0	40	100	180	1.84	40	0127156	400
40.0	10.0	+ 0/- 1	60.0	± 1.0	40	100	200	1.92	40	0127170	400
50.0	7.5	± 0.7	65.0	± 1.5	40	100	370	1.64	40	0127179	400
	9.0	± 0.7	68.0	± 1.5	40	100	280	2.04	40	0061501	■
60.0	10.0	± 0.7	80.0	± 1.5	40	100	340	2.72	40	0127183	400
65.0	10.0	± 0.7	85.0	± 1.5	40	100	380	2.93	40	0061500	■

Branding

