

PROJECTOR 40

CONSTRUCTION & ENVIRONMENT

Evacuation and material handling hoses



Applications

For spraying of mortar, and mixed concrete as well as dry products. Used as a service hose between pump and nozzle in transporting plaster, grout, and ready mixed concrete.

Advantages

- Light weight, flexible and is easy to handle.
- Abrasion resistant tube compound.
- Conductive inner tube compound gives increased safety for the operator.

Technical description

Inner tube: wear resistant NR, black, smooth.

Reinforcement: synthetic textile.

Cover: weather and wear resistant SBR, black, fabric impression.

Temperature range: - 30 °C to + 70 °C.

Electrical properties: conductive tube, $R < 2 \cdot 10^6 \Omega/m$.

Special properties: abrasion resistance of tube $< 70 \text{ mm}^3$ according to DIN 53516.

PROJECTOR 40

15/03/2007

ID	Wall thickness		OD		Working pressure	Bursting pressure	Bending radius	Weight	Length	Article number	Stock (■) or min. order
	mm	mm	mm	mm							
25.0	7.0	± 0.50	39.0	± 1.0	10	40	125	0.86	20	0201452	400
									40	0201453	400
25.0	9.5	± 0.50	44.0	± 1.0	10	40	120	1.29	20	0070670	400
									40	0070671	400
30.0	7.0	± 0.50	44.0	± 1.0	10	40	150	0.91	20	0201455	400
									40	0201456	400
32.0	10.0	± 0.50	52.0	± 1.0	10	40	150	1.65	20	0060192	■
									40	0060067	■
35.0	7.0	± 0.50	49.0	± 1.0	10	40	220	1.07	20	0070672	400
									40	0070673	400
38.0	10.0	± 0.50	58.0	± 1.0	10	40	170	1.88	40	5501052	400
40.0	10.0	± 0.50	60.0	± 1.0	10	40	180	1.97	20	0061716	■
									40	0061717	■
50.0	10.0	± 0.75	70.0	± 1.5	10	40	250	2.36	20	0061718	■
									40	0061719	■
60.0	10.0	± 0.75	80.0	± 1.5	10	40	290	2.64	20	0096832	■
									40	0096827	■
65.0	10.0	± 0.75	85.0	± 1.5	10	40	320	2.95	20	0061720	■
									40	0061721	■
70.0	10.0	± 0.75	90.0	± 1.5	10	40	350	3.20	20	0070674	200
									40	0070675	200
75.0	10.0	± 0.75	95.0	± 1.5	10	40	400	3.34	20	0070676	200
									40	0070677	200

Branding

