

PROJECTOR 60



CONSTRUCTION & ENVIRONMENT

Evacuation and material handling hoses

Applications

For spraying and transfer of mortar, light concrete, ready-mix and sand for mixer and transporter used for masonry.

Advantages

- Flexible and is easy to handle.
- Light weight.
- Highly abrasion resistant.
- Conductive inner tube compound.

Technical description

Inner tube: wear resistant NR, black, smooth.

Reinforcement: synthetic textile.

Cover: weather and wear resistant SBR, black, fabric impression.

Temperature range: - 30 °C to + 70 °C.

Electrical properties: conductive tube, $R < 2 \cdot 10^6 \Omega/m$.

Special properties: abrasion resistance of tube $< 70 \text{ mm}^3$ according to DIN 53516.

PROJECTOR 60

04/05/2007

ID	Wall thickness		OD		Working pressure	Bursting pressure	Bending radius	Weight	Length	Article number	Stock (■) or min. order
mm	mm		mm		bar	bar	mm	kg/m	m		m
65.0	10.0	± 0.75	85.0	± 1.5	20	60	320	2.94	20	5501065	■
89.0	10.5	± 0.75	110.0	± 1.5	20	60	500	4.13	20	5501066	■

Branding



⇨ upon availability

