

# SUPERVRAC TAN



## CONSTRUCTION & ENVIRONMENT

Evacuation and material handling hoses

### Applications

Pneumatic transport of bulk abrasive products. Discharge from road and rail tankers, and delivery to storage bins: cement, sand, lime, coal and also cereals, fertilizers, cattle feed and chemicals (PVC, dye stuffs, granulates, etc.).

### Advantages

- Light weight, flexible hose that coils flat.
- Excellent resistance to abrasion.
- Electrical conductivity ensured by a bonding braid.

### Technical description

**Inner tube:** heavy duty wear resistant NR, tan, smooth.

**Reinforcement:** synthetic textile.

**Cover:** weather resistant NR, black, fabric impression.

**Temperature range:** - 30 °C to + 70 °C.

**Electrical properties:** conductive built in wire.

### Couplings/Fittings

Factory fitted assemblies available with full flow couplings in 89 and 110 mm. For other assemblies, consult us.

## SUPERVRAC TAN

19/04/2007

ID	Wall thickness		OD		Working pressure	Bursting pressure	Weight	Length	Article number	Stock (■) or min. order
mm	mm		mm		bar	bar	kg/m	m		m
<b>75.0</b>	6.0	± 1.25	87.0	± 1.5	7	21	1.72	20	0070661	200
								40	0125111	200
<b>85.0</b>	6.0	± 1.25	97.0	± 1.5	7	21	1.81	20	0070662	200
								40	0070663	200
<b>89.0</b>	6.0	± 1.25	101.0	± 1.5	7	21	1.98	20	0060614	■
								40	0060615	■
<b>100.0</b>	6.0	± 1.25	112.0	± 1.2	7	21	2.24	20	0070664	200
								40	0070665	200
<b>110.0</b>	6.5	± 1.25	123.0	± 1.5	7	21	2.50	20	0060617	■
								40	0060618	■

### Branding

