

KLENET

AGRI & FOOD

Cleaning in food environment



Applications

Floor wash down and hot-water cleaning in food processing industries, canneries, dairies, slaughterhouses, etc.

Advantages

- Very good resistance to high temperatures.
- Smooth for easy handling with light-coloured, non-marking cover.
- Excellent resistance of the cover compound to animal and vegetable grease.
- International approvals.

Technical description

Inner tube: food grade quality, oil resistant NBR, white, smooth.

Reinforcement: synthetic textile.

Cover: oil and weather resistant NBR/PVC, blue, smooth.

Temperature range: - 20 °C to + 95 °C.

Standard/Approval:

CEE GUIDE for food contact.

FDA directives.

German legislation (BGvV).

Food grade approval from the French Institute of Poitiers (IANESCO).

KLENET

31/01/2008

ID	Wall thickness	OD	Working pressure	Bursting pressure	Bending radius	Weight	Length	Article number	Stock (■) or min. order		
mm	mm	mm	bar	bar	mm	kg/m	m		m		
13.0	± 0.5	4.2	21.4	± 0.7	10	30	80	0.30	20	0060962	■
									40	0060961	■
									60	0060952	4000
									120	0060953	■
16.0	± 0.7	4.5	25.0	± 0.8	10	30	95	0.38	20	0060964	■
									40	0060963	■
									60	0060954	3000
									120	0060955	■
19.0	± 0.7	4.7	28.4	± 0.8	10	30	115	0.48	20	0060966	■
									40	0060965	■
									60	0060956	■
									20	0060968	◇
25.0	± 1.0	5.0	35.0	± 1.1	10	30	155	0.62	40	0060967	■
									60	0060957	■

◇ upon availability

Branding

