

# TRELLOIL S

## CHEMICAL PETROCHEMICAL

Oil and petroleum/Tank truck suction and discharge



### Applications

Suction and discharge of petroleum products with aromatic content up to 50 % in all industrial applications.  
Road tanker equipment for oil and petrol deliveries.

### Advantages

- Easily cut to length and fitted with couplings.
- Light weight and flexible, even at cold temperature
- Dissipation of static electricity ensured by contact of built-in wire with the coupling.

### Technical description

**Inner tube:** oil and petrol resistant NBR, black, smooth.  
**Reinforcement:** synthetic textile with embedded steel helix.  
**Cover:** oil and weather resistant NBR/SBR, black, fabric impression.  
**Temperature range:** - 30 °C to + 80 °C.  
**Electrical properties:** built-in conductive wire.

## TRELLOIL S

20/03/2007

ID	Wall thickness	OD	Working pressure	Max. vacuum	Bursting pressure	Bending radius	Weight	Length	Article number	Stock (■) or min. order
mm	mm	mm	bar	bar	bar	mm	kg/m	m		m
25.0	5.25 ± 0.5	35.5 ± 1.0	10	0.9	30	50	0.84	20	5501411	400
								40	5501412	400
32.0	5.25 ± 0.5	42.5 ± 1.0	10	0.9	30	65	0.99	20	5501413	■
								40	5501414	■
35.0	5.75 ± 0.5	45.5 ± 1.0	10	0.9	30	70	1.06	20	5501489	400
								40	5501490	400
38.0	5.75 ± 0.5	49.5 ± 1.0	10	0.9	30	80	1.22	20	5501415	■
								40	5501416	■
40.0	5.75 ± 0.5	51.5 ± 1.0	10	0.9	30	85	1.27	20	5501491	■
								40	5501492	■
45.0	6.00 ± 0.5	57.0 ± 1.0	10	0.9	30	90	1.49	20	5501493	■
								40	5501494	■
50.0	6.50 ± 0.75	63.0 ± 1.0	10	0.9	30	125	1.81	20	5501417	■
								40	5501418	■
55.0	6.50 ± 0.75	68.0 ± 1.5	10	0.9	30	145	1.95	20	5501495	400
								40	5501496	400
60.0	6.50 ± 0.75	73.0 ± 1.5	10	0.9	30	150	2.21	20	5501419	■
								40	5501420	■
63.0	6.50 ± 0.75	76.0 ± 1.5	10	0.9	30	160	2.24	20	5501421	200
								40	5501422	200
70.0	7.50 ± 0.75	80.0 ± 1.5	10	0.9	30	210	2.86	20	5501497	■
								40	5501498	■
75.0	7.50 ± 0.75	90.0 ± 1.5	10	0.9	30	225	3.03	20	5501423	■
								40	5501424	■
80.0	7.50 ± 0.75	95.0 ± 1.5	10	0.9	30	280	3.21	20	5501425	■
								40	5501426	■
89.0	7.50 ± 0.75	104.0 ± 1.5	10	0.9	30	335	3.55	20	5501499	■
								40	5501500	■
100.0	7.50 ± 0.75	115.0 ± 1.5	10	0.9	30	400	3.94	20	5501427	■
								40	5501428	■

### Branding

