

SABLEX

CONSTRUCTION & ENVIRONMENT

Evacuation and material handling hoses



Applications

For cleaning and shot blasting castings, metal, stone, and concrete surfaces.

Advantages

- Small tolerances, therefore easy to couple.
- Longitudinally stable i.e. the length will not alter under pressure (unstable hoses result in the operator losing control when pressure is applied).
- Light weight and flexible for easy handling.
- Conductive inner tube compound gives increased safety for the operator, since there is no risk of wire breakage in use.

Technical description

Inner tube: wear resistant NR, black, smooth.

Reinforcement: synthetic textile.

Cover: weather and wear resistant SBR, black, fabric impression.

Temperature range: - 30 °C to + 70 °C.

Electrical properties: conductive tube, $R < 2 \cdot 10^6 \Omega/m$.

Special properties: abrasion resistance of tube $< 70 \text{ mm}^3$ according to DIN 53 516.

SABLEX

21/08/2007

ID	Wall thickness		OD		Working pressure	Bursting pressure	Bending radius	Weight	Length	Article number	Stock (■) or min. order
	mm	mm	mm	mm							
13.0	7.0	± 0.50	27.0	± 1.0	12	40	65	0.58	20	0028711	■
										40	0028712
16.0	7.0	± 0.50	30.0	± 1.0	12	40	80	0.68	20	0028719	400
									40	0028720	400
19.0	7.5	± 0.50	34.0	± 1.0	12	40	100	0.78	20	0028745	■
									40	0028746	■
25.0	7.0	± 0.50	39.0	± 1.0	12	40	125	0.86	20	0060969	■
									40	0060970	■
32.0	8.0	± 0.50	48.0	± 1.0	12	40	160	1.30	20	0060971	■
									40	0060972	■
32.0	11.0	± 0.50	54.0	± 1.0	12	40	140	1.85	20	0070785	◇
									40	0070786	■
35.0	9.0	± 0.50	53.0	± 1.0	12	40	190	1.57	40	0070788	400
38.0	10.0	± 0.50	58.0	± 1.0	12	40	170	1.89	20	0070789	■
									40	0070790	■
40.0	10.0	± 0.50	60.0	± 1.0	12	40	180	1.97	20	0028786	■
									40	0028787	■
42.0	9.0	± 0.50	60.0	± 1.0	12	40	240	1.81	20	0070791	400
									40	0070792	400
50.0	10.0	± 0.75	70.0	± 1.5	12	40	250	2.36	20	0060973	■
									40	0060974	■
63.0	10.0	± 0.75	83.0	± 1.5	12	40	325	2.90	40	0060077	200
65.0	10.0	± 0.75	85.0	± 1.5	12	40	320	2.95	20	0070797	200
									40	0070798	200
76.0	10.0	± 0.75	96.0	± 1.5	12	40	400	3.42	20	0028851	◇
									40	0070784	■
102.0	10.0	± 0.75	122.0	± 1.5	10	40	550	4.40	20	0028859	◇
									40	0028860	■

Branding

◇ upon availability

