

METALAIR

INDUSTRIAL MAINTENANCE

Air/Compressed air applications



Applications

Heavy duty handling of oil charged compressed air (tanker duty).
High pressure compressors and other equipment used on public works sites.

Advantages

- Very robust due to the steel reinforcement.
- Resistant to atmospheric conditions and contact with greasy floors.
- Resistant to mineral oils.

Technical description

Inner tube: NBR, black, smooth.

Reinforcement: steel braids or steel cords.

Cover: SBR, yellow, fabric impression.

Temperature range: - 30 °C to + 95 °C.

METALAIR

31/05/2007

ID	Wall thickness	OD	Working pressure	Bursting pressure	Bending radius	Weight	Length	Article number	Stock (■) or min. order	
mm	mm	mm	bar	bar	mm	kg/m	m		m	
19.0	-0/+1.0	6.75	32.5 ±1.5	40	160	115	0.84	20	0075408	1000
								40	0070641	1000
25.0	-0/+1.0	7.00	39.0 ±1.5	40	160	150	1.12	20	0127603	1000
								40	0070642	1000
32.0	-0/+1.0	7.00	46.0 ±1.5	40	160	230	1.45	20	0070643	500
								40	0070644	500
38.0	-0/+1.0	7.50	53.0 ±1.5	40	160	280	1.75	20	0070645	500
								40	0070646	500
50.0	-0/+1.5	8.00	66.0 ±1.5	40	160	300	2.43	20	0075418	2 x 20
								40	0070647	■
60.0	-0/+1.5	8.00	76.0 ±1.5	40	160	380	2.98	40	0075425	200

Branding

