

TRELLVAST

CHEMICAL PETROCHEMICAL

Steam



Applications

For heavy duty industrial steam cleaning and circulation of saturated or superheated steam at temperatures up to + 164 °C/ WP 6 bar.

Advantages

- Resistant to abrasion and atmospheric conditions.
- Flexible textile reinforced steam hose.

Technical description

Inner tube: EPDM for ID ≤ 25 mm, SBR for ID > 25 mm, black, smooth.

Reinforcement: synthetic textile.

Cover:

ID ≤ 25 mm: EPDM, black, smooth.

ID > 25 mm: SBR, black, fabric impression.

Temperature range:

Water: - 40 °C to + 120 °C, WP = 20 bar

Saturated steam or superheated steam: + 164 °C/6 bar.

Electrical properties: conductive tube and cover, R < 10⁶ Ω/Ig.

Standard/Approval: EN ISO 6134 type 1, class A.

TRELLVAST

19/03/2007

ID	Wall thickness	OD	Working pressure	Bursting pressure	Bending radius	Weight	Length	Article number	Stock (■) or min. order	
mm	mm	mm	bar	bar	mm	kg/m	m		m	
9.5	± 0.5	6.00	21.5 ± 1.0	6	60	120	0.30	20	5015601	■
								40	5015602	4000
13.0	± 0.5	6.00	25.0 ± 1.0	6	60	130	0.48	20	5015536	■
								40	5015537	4000
16.0	± 0.5	7.00	30.0 ± 1.0	6	60	160	0.67	20	5015577	■
								40	5015578	3000
19.0	± 0.5	7.00	33.0 ± 1.0	6	60	190	0.77	20	5015538	■
								40	5015539	■
25.0	± 0.5	7.50	40.0 ± 1.0	6	60	250	1.06	20	5015540	■
								40	5015541	■
* 32.0	- 0/+ 1	8.25	48.5 ± 1.0	6	60	250	1.25	20	0202365	■
								40	0202366	■
* 38.0	- 0/+ 1	8.75	55.5 ± 1.0	6	60	300	1.49	20	0202368	200
								40	0202369	200
* 40.0	- 0/+ 1	8.75	57.5 ± 1.0	6	60	320	1.54	20	0202377	■
								40	0202378	■
* 50.0	- 0/+ 1	8.25	66.5 ± 1.5	6	60	400	1.79	20	0202371	■
								40	0202372	■
* 60.0	- 0/+ 1	8.75	77.5 ± 1.5	6	60	500	2.20	20	0202374	■
								40	0202375	■

* non standard compliance with EN ISO 6134

Embossed branding for ID ≤ 25 mm



Branding for ID > 25 mm



and embossed: TRELLEBORG - STEAM - 6 bar - 164 °C - ID - Ω - quarter/year

