

# SUPERVRAC AL



## CONSTRUCTION & ENVIRONMENT

Evacuation and material handling hoses

### Applications

Pneumatic transport of bulk abrasive products for the food industry.  
Discharge from road and rail tankers, and delivery to storage bins: foodstuffs (sugar, flour, milk powder, cattle feed, etc.) and chemicals (fertilizers, granulates, PVC, dye stuffs etc.).

### Advantages

- Light weight, flexible hose that coils flat.
- Excellent resistance to abrasion.
- Electrical conductivity ensured by a bonding braid.

### Technical description

**Inner tube:** foodstuffs, abrasive resistant NR, white, smooth.

**Reinforcement:** synthetic textile.

**Cover:** weather resistant NR, black, fabric impression.

**Temperature range:** - 30 °C to + 80 °C.

**Electrical properties:** conductive built in wire.

**Standard/Approval:**

Approval from the French Institute of Poitiers (IANESCO).

Inner tube fully complies with FDA.

### Couplings/Fittings

Factory fitted assemblies available with full flow couplings in 89 and 110 mm bore hoses. For other assemblies, consult us.

## SUPERVRAC AL

21/06/2007

ID	Wall thickness		OD		Working pressure	Bursting pressure	Weight	Length	Article number	Stock (■) or min. order
mm	mm		mm		bar	bar	kg/m	m		m
75.0	6.0	± 1.00	87.0	± 1.5	7	21	1.80	20	0070657	200
								40	0070658	200
75.0	9.0	± 1.25	93.0	± 1.5	7	21	2.78	20	0060916	◇
								40	0060913	■
85.0	6.0	± 1.00	97.0	± 1.5	7	21	1.99	20	0070659	200
								40	0070660	200
89.0	6.0	± 1.00	101.0	± 1.5	7	21	2.07	20	0060620	■
								40	0060621	■
100.0	6.0	± 1.00	112.0	± 1.5	7	21	2.35	20	0126668	200
								40	0070317	200
100.0	9.0	± 1.25	118.0	± 1.5	7	21	3.60	20	0060914	■
								40	0060915	■
110.0	6.5	± 1.25	123.0	± 1.5	7	21	2.63	20	0060623	■
								40	0060624	■

◇ upon availability

### Branding

