

# TRELLVAC Handler MD

## CONSTRUCTION & ENVIRONMENT

Evacuation and material handling hoses



### Applications

Medium duty working hose on vacuum cleaning trucks for use at the work site.

### Advantages

- Light and flexible with good wear resistance.
- Specially designed for light materials transport and very easy handling.

### Technical description

**Inner tube:** wear resistant NR, black, smooth.

**Reinforcement:** synthetic textile, woven fabric with embedded steel helix.

**Cover:** wear and weather resistant SBR, black, corrugated.

**Temperature range:** - 30 °C to + 90 °C.

**Electrical properties:** non conductive. The helix can be connected to couplings in both ends.

### Complementary information

Diameters 51, 76, 102, 127, 152 and 204 mm could be delivered in roll of 40 m, except diameter 204 mm (roll of 20 m). Min. quantity: 120 m per diameter.

Conductive hose upon request with built-in conductive wire for diameters 76, 102, 127, 152 and 204 mm. Delivery lengths: 40 m, except for diameter 204 mm (20 m). Min. quantity: 120 m per diameter.

**Resistance** ○○○○

**Flexibility** ○○○

**Weight** ○○○

## TRELLVAC Handler MD

27/04/2007

ID		OD *		Working pressure	Bursting pressure	Max. vacuum	Bending radius	Weight	Length	Article number	Stock (■) or min. order
	mm	mm		bar	bar	bar	mm	kg/m	m		m
<b>76.0</b>	+ 1.5/- 1.5	91.0	± 1.5	5	15	0.9	295	2.0	12	1776690	■
<b>102.0</b>	+ 1.5/- 1.5	118.0	± 1.5	5	15	0.9	395	2.9	12	1776700	■
<b>127.0</b>	+ 1.5/- 1.5	144.0	± 1.5	5	15	0.9	495	3.9	12	1973590	■
<b>152.0</b>	+ 1.5/- 1.5	167.0	± 1.5	5	15	0.9	595	4.5	12	1776710	■
<b>178.0</b>	+ 1.5/- 1.5	195.0	± 1.5	5	15	0.9	695	5.2	12	2303130	200
<b>204.0</b>	+ 1.5/- 1.5	224.0	± 1.5	5	15	0.9	795	7.0	12	1776720	■

\* OD measured on top of corrugation

### Branding

