

TRELLVAC Handler LD



CONSTRUCTION & ENVIRONMENT

Evacuation and material handling hoses

Applications

For industrial vacuum cleaners and cleaning systems.
Useful for suction of drainage sludge, sand etc.

Advantages

- Light and flexible design.
- Very good wear resistance.
- Especially useful when low weight and easy handling are valued.

Technical description

Inner tube: wear resistant NR, black, smooth.

Reinforcement: synthetic textile cords with embedded steel helix.

Cover: wear and weather resistant SBR, black, corrugated.

Temperature range: - 30 °C to + 80 °C.

Electrical properties: non conductive. The helix can be connected to couplings in both ends.

Resistance ○○○

Flexibility ○○○○

Weight ○○○○

TRELLVAC Handler LD

26/04/2007

ID		OD *		Working pressure	Bursting pressure	Max. vacuum	Bending radius	Weight	Length	Article number	Stock (■) or min. order
mm		mm		bar	bar	bar	mm	kg/m	m		m
51.0	+ 1.5/- 1.5	61.5	± 1.5	5	15	0.9	85	0.9	20	5500748	■
									40	2914510	■
60.0	+ 1.5/- 1.5	70.5	± 1.5	5	15	0.9	105	1.1	20	5500749	200
									40	2914520	200
63.0	+ 1.5/- 1.5	73.5	± 1.5	5	15	0.9	110	1.2	20	5500750	■
									40	2891580	■
76.0	+ 1.5/- 1.5	87.0	± 1.5	5	15	0.9	135	1.5	20	5500751	■
									40	2913940	■

* OD measured on top of corrugation

Branding

