

SILEX

CONSTRUCTION & ENVIRONMENT

Blasting and guniting



Applications

Pneumatic discharge of powder (lime, cement, fertilizers, etc.), grain, sand, silica, minerals, or sized products (fertilizers, PVC granulates, cereals, etc.).
Sand and shot blasting of buildings and metal parts.

Technical description

Inner tube: wear resistant NR, black, smooth.

Reinforcement: synthetic textile.

Cover: weather resistant NR, grey, fabric impression.

Temperature range: - 30 °C to + 70 °C.

Electrical properties: conductive tube and built-in conductive wire.

Advantages

- Highly resistant to abrasion due to friction and atmospheric conditions.
- Electrical conductivity is assured by the tube compound together with a metal braid.
- Excellent resistance to bending and twisting.

SILEX

18/10/2007

ID		Wall thickness	OD		Working pressure	Bursting pressure	Bending radius	Weight	Length	Article number	Stock (■) or min. order
mm		mm	mm		bar	bar	mm	kg/m	m		m
20.0	-0/+1.0	10.50	41.0	±1.0	10	30	120	1.15	20	0125393	400
									40	0126564	400
25.0	-0/+1.0	10.50	46.0	±1.0	10	30	150	1.33	20	0072310	■
									40	0072312	400
30.0	-0/+1.0	10.50	51.0	±1.0	10	30	180	1.45	20	0072317	■
									40	0072319	400
35.0	-0/+1.0	10.50	56.0	±1.0	10	30	210	1.75	20	0072324	■
									40	0072326	400
40.0	-0/+1.0	10.50	61.0	±1.0	10	30	240	1.85	20	0072330	■
									40	0072332	■
50.0	-0/+1.0	11.75	73.5	±1.0	10	30	400	2.60	20	0072342	■
									40	0072344	■
60.0	-0/+1.5	12.50	85.0	±1.5	10	30	600	3.15	20	0061502	■
65.0	-0/+1.5	13.25	91.5	±1.5	10	30	650	3.50	20	0070073	80
70.0	-0/+1.5	14.25	98.5	±1.5	10	30	700	3.96	20	0061503	■
80.0	-0/+2.0	15.50	111.0	±1.5	10	30	800	4.74	10	0061504	■
90.0	-0/+2.0	15.50	121.0	±1.5	10	30	1070	5.26	10	0061505	■
100.0	-0/+2.0	15.50	131.0	±1.5	10	30	1200	5.75	10	0061506	■
110.0	-0/+2.0	15.00	140.0	±1.5	10	30	1320	7.24	10	0061507	■
125.0	-0/+2.0	15.00	155.0	±1.5	10	30	1500	8.08	10	0061508	40

Branding

