

# ALIKLER D

## AGRI & FOOD

### Food hoses



### Applications

High pressure discharge of liquid foods-tuffs such as milk, beer, oil, fat, wine, cider, fruit juice, and alcohol up to 96 %.  
Suction on unloading bays in dairies.  
Equipment of processing and filling plants, and liquid foodstuff tankers.

### Advantages

- Smooth, seamless, white, multipurpose food grade tube that does not propagate bacterial growth.
- Able to recover its shape after accidental squeeze.
- Changes in temperature have little effect due to the qualities of the rubber compound.
- Resistant to cleaning with detergents at temperatures up to 130 °C (during several minutes).
- Non-marking, abrasion resistant cover.
- International approvals.

### Technical description

**Inner tube:** food grade, oil resistant NBR, white, smooth.  
**Reinforcement:** synthetic textile with embedded PET helix for ID  $\geq$  50 mm.  
**Cover:** oil and weather resistant NBR/PVC, blue, fabric impression.  
**Temperature range:** - 30 °C to + 100 °C.  
**Standard/Approval:**  
CEE GUIDE for food contact.  
FDA directives.  
German legislation (BGvV).  
Food grade approval from the French Institute of Poitiers (IANESCO).

### Couplings/Fittings

Specially designed fittings are available, please contact us for further information in order to get optimum connections.

## ALIKLER D

06/02/2008

ID	Wall thickness	OD	Working pressure	Bursting pressure	Max. vacuum	Bending radius	Weight	Length	Article number	Stock (■) or min. order
mm	mm	mm	bar	bar	bar	mm	kg/m	m		m
<b>32.0</b> -0/+1	6.0	44.0 ±1.5	15	40	0.7	220	1.00	20	0061567	■
								40	0061568	■
<b>38.0</b> -0/+1	6.5	51.0 ±1.5	15	40	0.7	265	1.20	20	0061569	■
								40	0061570	■
<b>50.0</b> -0/+1	8.0	66.0 ±1.5	15	40	0.7	300	1.97	20	0061571	■
								40	0061572	■
<b>63.0</b> -0/+1	8.0	79.0 ±1.5	15	40	0.7	450	2.38	20	0061573	■
								40	0061574	■
<b>75.0</b> -0/+1	8.0	91.0 ±1.5	15	40	0.7	525	2.85	20	0061575	■
								40	0061576	■
<b>100.0</b> -0/+1	8.5	117.0 ±1.5	15	40	0.7	700	3.81	20	0061577	■
								40	0061578	■

### Branding

