

TRELLVAC Extractor HD



CONSTRUCTION & ENVIRONMENT

Evacuation and material handling hoses

Applications

Universal material handling hose for suction of shavings, sand, dust, and powder etc.
Applications include sawmills, chip board, and wood veneer plants, fiberboard plants etc.

Advantages

- Light and flexible design with steel helix.
- Good bending radius.
- Especially useful when low weight and easy handling in combination with good abrasion resistance are valued.

Technical description

Inner tube: wear resistant SBR, black, smooth.

Reinforcement: synthetic textile, woven fabric, with embedded steel helix.

Cover: wear and weather resistant SBR, black, corrugated.

Temperature range: - 40 °C to + 90 °C.

Electrical properties: conductive tube, $R < 10^6 \Omega/m$.

Resistance ⚡⚡⚡⚡

Flexibility ⚡⚡⚡⚡

Weight ⚡⚡⚡⚡

TRELLVAC Extractor HD

26/04/2007

ID		OD *		Max. vacuum	Bending radius	Weight	Length	Article number	Stock (■) or min. order
mm		mm		bar	mm	kg/m	m		m
38.0	+ 1.5/- 1.5	47.5	± 1.0	0.9	50	0.67	12	0124823	■
51.0	+ 1.5/- 1.5	60.5	± 1.0	0.9	75	0.87	12	0129711	■
63.0	+ 1.5/- 1.5	73.0	± 1.0	0.9	100	1.10	12	0124849	■
76.0	+ 1.5/- 1.5	86.0	± 1.5	0.9	120	1.31	12	0124825	■
102.0	+ 1.5/- 1.5	113.0	± 1.5	0.9	150	1.93	12	0125779	■
127.0	+ 1.5/- 1.5	138.0	± 1.5	0.7	175	2.37	12	0124828	36
152.0	+ 1.5/- 1.5	163.0	± 1.5	0.4	200	2.82	12	0124829	■

* OD measured on top of corrugation

Branding

