

TRELLBLAST S

CONSTRUCTION & ENVIRONMENT

Blasting and guniting



Applications

For cleaning and shot blasting castings, metal, stone, and concrete surfaces.

Advantages

- Light weight and flexible for easy handling.
- Conductive inner tube compound gives increased safety for the operator, since there is no risk of wire breakage in use.

Technical description

Inner tube: wear resistant NR, black, smooth.

Reinforcement: synthetic textile.

Cover: weather and wear resistant SBR, black, fabric impression.

Temperature range: - 30 °C to + 70 °C.

Electrical properties: conductive tube, $R < 2.10^6 \Omega/m$.

Special properties: abrasion resistance of tube $< 70 \text{ mm}^3$ according to DIN 53516.

TRELLBLAST S

04/05/2007

ID	Wall thickness		OD		Working pressure	Bursting pressure	Bending radius	Weight	Length	Article number	Stock (■) or min. order
mm	mm	mm	mm	mm	bar	bar	mm	kg/m	m		m
13.0	7.0	± 0.5	27.0	± 1	10	30	65	0.56	40	5026067	■
16.0	7.0	± 0.5	30.0	± 1	10	30	80	0.68	40	5026068	■
19.0	7.5	± 0.5	34.0	± 1	10	30	100	0.74	40	5501321	■
25.0	7.0	± 0.5	39.0	± 1	10	30	125	0.86	40	5501322	■
32.0	8.0	± 0.5	48.0	± 1	10	30	160	1.30	40	5501323	■

Branding



⇨ upon availability

