

# ALIKLER

## AGRI & FOOD

### Food hoses



### Applications

Suction and discharge of liquid foodstuffs such as wine, beer, milk, oil, fats, cider, fruit juice, and alcohol up to 96 %.

For unloading bays, processing and filling plants, and liquid foodstuff tankers.

Additional air line (for tanker hose blast cleaning) on road tankers carrying bulk powdered products (not compressor line) at temperatures up to + 120 °C.

### Advantages

- A smooth, seamless, white, multipurpose food-grade tube that does not propagate bacterial growth.
- Flexible and easy to handle.
- Excellent resistance to kinking.
- Changes in temperature have little effect due to the qualities of the rubber compound.
- Resistant to cleaning with detergents at temperatures up to + 130 °C (during several minutes).
- Non-marking, abrasion-resistant cover.
- International approvals.

### Technical description

**Inner tube:** food grade quality, oil resistant NBR, white, smooth.

**Reinforcement:** synthetic textile with embedded steel helix.

**Cover:** oil and weather resistant NBR/PVC, blue, fabric impression.

**Temperature range:** - 30 °C to + 100 °C.

**Standard/Approval:**

CEE GUIDE for food contact.

FDA directives.

German legislation (BGvV).

Food grade approval from the French Institute of Poitiers

(IANESCO).

### Couplings/Fittings

Specially designed fittings are available, please contact us for further information in order to get optimum connections.

## ALIKLER

09/10/2007

ID	Wall thickness	OD	Working pressure	Bursting pressure	Max. vacuum	Bending radius	Weight	Length	Article number	Stock (■) or min. order	
mm	mm	mm	bar	bar	bar	mm	kg/m	m		m	
25.0	-0/+1	6.00	37.0 ±1	10	30	0.9	50	0.97	20	0123024	■
									40	0123027	■
32.0	-0/+1	6.00	44.0 ±1	10	30	0.9	65	1.15	20	0061300	■
									40	0061301	■
38.0	-0/+1	6.00	50.0 ±1	10	30	0.9	75	1.32	20	0061302	■
									40	0061303	■
43.0	-0/+1	6.00	55.0 ±1	10	30	0.9	110	1.46	20	0061351	■
									40	0061352	■
45.0	-0/+1	6.00	57.0 ±1	10	30	0.9	115	1.50	20	0061304	■
									40	0061305	■
50.0	-0/+1	6.00	62.0 ±1.5	10	30	0.9	125	1.85	20	0061306	■
									40	0061307	■
53.0	-0/+1	6.00	65.0 ±1.5	10	30	0.9	135	1.94	20	0061308	■
									40	0061309	■
60.0	-0/+1	6.50	73.0 ±1.5	10	30	0.9	150	2.26	20	0061353	■
									40	0061354	■
63.0	-0/+1	6.50	76.0 ±1.5	10	30	0.9	160	2.36	20	0061310	■
									40	0061311	■
70.0	-0/+1	7.25	84.5 ±1.5	10	30	0.9	210	3.21	20	0061355	■
									40	0061356	■
75.0	-0/+1	7.25	89.5 ±1.5	10	30	0.9	225	3.40	20	0061312	■
									40	0061313	■
89.0	-0/+1	7.75	104.5 ±1.5	10	30	0.9	320	4.02	20	0061314	■
									40	0061315	■
100.0	-0/+1	7.75	115.5 ±1.5	10	30	0.9	500	4.49	20	0061316	■
									40	0061317	■
125.0	-0/+1	10.25	145.5 ±2.0	10	30	0.9	700	7.44	10	5500647	■
									20	5500648	■
150.0	-0/+1	10.75	171.5 ±2.0	10	30	0.9	800	9.15	10	5500649	■
									20	5500650	■

### Branding



and embossed: TRELLEBORG - ALIKLER - ND - WP 10 bar - week/year

