

SUPERVRAC

CONSTRUCTION & ENVIRONMENT

Bulk tank truck discharge



Applications

Pneumatic transport of bulk abrasive products.
Discharge from road and rail tankers and delivery to storage bins (cement, sand, limestone, coal, etc.).

Advantages

- Light weight, flexible hose that coils flat.
- Excellent resistance to abrasion.
- Static conductive tube.

Technical description

Inner tube: wear resistant NR, black, smooth.

Reinforcement: synthetic textile.

Cover: weather resistant NR, black, fabric impression.

Temperature range: - 30 °C to + 90 °C.

Electrical properties: conductive tube, $R < 10^6 \Omega/m$.

Couplings/Fittings

Factory fitted assemblies available with full flow couplings in 89 and 110 mm. For other assemblies, consult us.

SUPERVRAC

19/04/2007

ID	Wall thickness		OD		Working pressure	Bursting pressure	Weight	Length	Article number	Stock (■) or min. order
mm	mm	mm	mm	mm	bar	bar	kg/m	m		m
75.0	6.75	± 1.25	88.5	± 2.0	7	21	1.83	20	0060675	■
								40	0060674	■
75.0	9.00	± 1.00	93.0	± 1.5	7	21	2.75	20	0060189	■
								40	0060193	■
85.0	6.00	± 1.00	97.0	± 1.5	7	21	2.03	20	0129699	200
								40	0129700	200
89.0	6.25	± 1.25	101.5	± 2.0	7	21	2.07	20	0060682	■
								40	0060683	■
100.0	6.00	± 1.00	112.0	± 1.5	7	21	2.40	20	0129701	■
								40	0129702	■
100.0	9.00	± 1.00	118.0	± 1.5	7	21	3.58	20	0060194	■
								40	0060195	■
110.0	6.50	± 1.25	123.0	± 2.0	7	21	2.71	20	0060684	■
127.0	8.50	± 1.25	144.0	± 2.0	7	21	4.20	20	0060685	200
								40	0060686	200
152.0	8.50	± 1.25	169.0	± 2.0	7	21	5.00	20	0060689	200
								40	0060690	200

Branding

