

# TRELLVAC Transporter HD



## CONSTRUCTION & ENVIRONMENT

Evacuation and material handling hoses

### Applications

Transport hose for vacuum cleaning trucksand in stationary systems in straight orbend positions in all types of industries. Extraction and transport of abrasive materials such as sand, gravel, stone, sludge and powder.

### Advantages

- Fully rot resistant reinforcement.
- Smooth cover.
- Flexible and very high abrasion resistance.
- Can be used for vacuum and discharge.

**Resistance** ★★★★★

**Flexibility** ★★★

**Weight** ★★

### Technical description

**Inner tube:** wear resistant NR/SBR, black, smooth.

**Reinforcement:** synthetic textile cords with embedded steel helix.

**Cover:** wear and weather resistant SBR, black, fabric impression.

**Temperature range:** - 40 °C to + 90 °C.

**Electrical properties:** conductive tube and cover,  $R < 10^6 \Omega/m$ , and built-in conductive wire.

## TRELLVAC Transporter HD

27/04/2007

ID	OD	Working pressure	Bursting pressure	Max. vacuum	Bending radius	Weight	Length	Article number	Stock (■) or min. order		
mm	mm	bar	bar	bar	mm	kg/m	m		m		
<b>51.0</b>	± 1.5	64.0	± 1.0	5	15	0.9	210	1.8	20	5500753	■
									40	5500752	■
<b>63.0</b>	± 1.5	76.0	± 1.0	5	15	0.9	250	2.2	20	5500755	■
									40	5500754	■
<b>76.0</b>	± 1.5	90.0	± 1.5	5	15	0.9	300	2.8	20	5500757	■
									40	5500756	■
<b>90.0</b>	± 1.5	104.0	± 1.5	5	15	0.9	350	3.4	20	5500759	■
									40	5500758	■
<b>102.0</b>	± 1.5	117.0	± 1.5	5	15	0.9	400	3.8	20	5500761	■
									40	5500760	■
<b>108.0</b>	± 1.5	123.0	± 2.0	5	15	0.9	430	4.1	20	5500763	■
									40	5500762	■
<b>116.0</b>	± 1.5	131.0	± 2.0	5	15	0.9	450	4.6	20	5500765	■
									40	5500764	■
<b>127.0</b>	± 1.5	143.0	± 2.0	5	15	0.9	510	5.3	20	5500767	■
									40	5500766	■
<b>140.0</b>	± 1.5	156.0	± 2.0	5	15	0.9	580	5.7	20	5500769	80
									40	5500768	80
<b>152.0</b>	± 1.5	168.0	± 2.0	5	15	0.9	640	6.3	20	5500771	■
									40	5500770	■
<b>165.0</b>	± 1.5	182.0	± 2.0	3	10	0.9	700	7.2	10	5500772	80
<b>204.0</b>	± 1.5	222.0	± 2.0	3	10	0.9	820	9.9	10	5501132	■

### Branding

