

SUPERVAST

CHEMICAL PETROCHEMICAL

Steam



Applications

For heavy duty industrial cleaning and circulation of saturated and superheated steam in heating systems in applications where the hose is exposed to oil.

Used in the petrochemical, building, shipyard, and chemical industries.

Advantages

- Oil resistant cover.
- Multipurpose hose.
- Highly flexible.
- Very high temperature resistance.
- Chemical resistant.
- Durable and safe performance.
- Fulfills international standards.

Technical description

Inner tube: EPDM, black, smooth.

Reinforcement: steel, braided.

Cover: CSM, red, fabric impression.

Temperature range:

Water: - 40 °C to + 120 °C, WP = 60 bar.

Saturated steam: + 210 °C/18 bar.

Superheated steam: + 230 °C/18 bar.

Electrical properties: conductive tube, $R < 10^6 \Omega/\text{lg}$.

Standard/Approval: EN ISO 6134 type 2, Cat. B.

SUPERVAST

20/08/2007

ID	Wall thickness	OD	Working pressure (steam)	Working pressure (water)	Bursting pressure (water)	Bending radius	Weight	Length	Article number	Stock (■) or min. order	
mm	mm	mm	bar	bar	bar	mm	kg/m	m		m	
19.0	± 0.5	7.0	33 ± 1.0	18	60	180	190	0.77	20	5015531	■
									30	5015570	■
25.0	± 0.5	7.0	40 ± 1.0	18	60	180	250	1.06	20	5015534	■

Red embossed branding

