

TU 20

Multi-Purpose Mineral Oil Hose

Application:

- ④ Flexible delivery hose for unleaded fuels (EN228:2004), diesel (EN 590:2004) and heating oils (DIN 51 603 parts 1 - 5) and compressed air.
- ④ Multi-purpose hose on an NBR-basis for diverse applications in industry, garages, filling stations and automobile repair shops.

Standard/approval:

- ④ BS 2050:1978.
- ④ BS ISO 2878:2005 .

Notice:

- ④ Electrically conductive: Resistance $R < 10^6 \text{ Ohm/m}$ (according to EN ISO 8031:1997).
- ④ ATTENTION: Not to be used as a petrol pump hose.



Temperature range: -40°C / +80°C.

Safety factor: 3 : 1

Tube: NBR, black, smooth, electrically conductive.

Reinforcement: Textile spiral construction.

Cover:

Marking: Continuous marking, white:
"SEMPERIT S TU 20 NBR Öl/Luft Oil/Air PN 20 bar
Conductive $R < 10^6 \text{ Ohm/m}$ ".

Article number	Internal-Ø in		Wall width in mm	External-Ø in mm	Work. pressure (max.) bar	Number of inserts	Bending radius (min.) in mm	Weight approx. kg/m	Coil length (max.) m
	mm	inches							
68179 0649	6,0	1/4	4,0	14,0	20	2	40	0,16	100
68179 0849	8,0	5/16	4,0	16,0	20	2	50	0,20	100
68179 1040	10,0	3/8	4,0	18,0	20	2	60	0,22	50
68179 1340	13,0	1/2	4,0	21,0	20	2	80	0,28	50
68179 1645	16,0	5/8	4,5	25,0	20	2	100	0,38	50
68179 1950	19,0	3/4	5,0	29,0	20	2	120	0,50	50
68179 2555	25,0	1	5,5	36,0	20	2	150	0,69	50

Please note: General information about our range of products can be found in the appendix to this catalogue. Before using with new or untested media, or before using in applications that are not covered in the product information, written advice must first be obtained from a specialist dealer or a Semperit application engineer. All products must be inspected regularly for operational safety. For safety reasons, hoses must be replaced in the event of damage, especially if the cover is damaged. All products must be stored and maintained according to our storage, care and maintenance instructions, and according to DIN 7716:1982. We are constantly developing and improving our products for our customers. For the latest product information, please visit our website www.semperflex.com regularly or contact one of our specialist dealers or Semperit application engineers. Contracts are agreed according to our general terms and conditions. Subject to change without notice.

Important notice: This catalogue has been prepared with the greatest care in order to provide you with all the information you need. The information contained herein incorporates the latest state-of-the-art technology, and is the result of trials and tests carried out over many years, or conforms to the resistance requirements of the media listed as set out in ISO TR 7620:2005 (E). The individual conditions of use affect the use of each product. They therefore only ensure the safety that can be expected assuming that the specifications in our written product information, the specifications regarding resistance to chemicals and our cleaning procedures are all complied with. We cannot guarantee this level of safety in the event of improper handling, e.g. squashing, rupturing, stretching or filling with media that are not permitted. Unless specified otherwise, all hoses are manufactured to EN ISO 1307:2006.