

# TRELLVAC Extractor LD

## CONSTRUCTION & ENVIRONMENT

Evacuation and material handling hoses



### Applications

Universal ducting hose for dust, wood chips, small particles and various types of gas.

### Advantages

- Light and flexible.
- Excellent bending radius.
- Especially useful when low weight and easy handling are valued.

### Technical description

**Inner tube:** wear resistant SBR, black, smooth.

**Reinforcement:** synthetic textile with embedded steel helix.

**Cover:** wear and weather resistant SBR, black, corrugated.

**Temperature range:** - 40 °C to + 90 °C.

**Electrical properties:** conductive tube,  $R < 10^6 \Omega/m$ .

Resistance ☼☼

Flexibility ☼☼☼☼☼

Weight ☼☼☼☼☼

## TRELLVAC Extractor LD

29/01/2008

ID		OD *		Max. vacuum	Bending radius	Weight	Length	Article number	Stock (■) or min. order
mm		mm		bar	mm	kg/m	m		m
38.0	+ 1.5/- 1.5	44.5	± 0.8	0.9	45	0.44	12	0025890	■
51.0	+ 1.5/- 1.5	57.5	± 0.8	0.9	70	0.58	12	0025908	■
63.0	+ 1.5/- 1.5	70.0	± 0.8	0.9	95	0.74	12	0025916	■
76.0	+ 1.5/- 1.5	83.0	± 0.8	0.9	115	0.88	12	0025932	■
90.0	+ 1.5/- 1.5	97.5	± 0.8	0.9	125	1.04	12	0025965	■
102.0	+ 1.5/- 1.5	110.0	± 0.8	0.9	145	1.37	12	0025973	■
113.0	+ 1.5/- 1.5	121.0	± 0.8	0.9	155	1.50	12	0025981	■
127.0	+ 1.5/- 1.5	135.0	± 0.8	0.7	170	1.68	12	0026005	■
152.0	+ 1.5/- 1.5	160.0	± 0.8	0.4	195	2.00	12	0026013	■
178.0	+ 1.5/- 1.5	186.0	± 0.8	0.25	220	2.33	12	0026021	12
204.0	+ 1.5/- 1.5	212.0	± 0.8	0.15	245	2.67	12	0026039	■

\* OD measured on top of corrugation

#### Branding

