

ASPIKLER N

CONSTRUCTION & ENVIRONMENT

Drain and sewer cleaning



Applications

For sewer suction.

Also for suction or delivery of abrasive materials on stationary systems and for cassette applications on sewer cleaning vehicles.

Advantages

- High resistance to abrasive environment and abrasive transportation media.
- Suitable both for suction and pressure.

Technical description

Inner tube: SBR, black, smooth.

Reinforcement: synthetic textile cords with embedded steel helix.

Cover: SBR/NR, black, fabric impression.

Temperature range: - 30 °C to + 80 °C.

ASPIKLER N

27/05/2008

ID	Wall thickness	OD	Working pressure	Bursting pressure	Max. vacuum	Bending radius	Weight	Length	Article number	Stock (■) or min. order	
mm	mm	mm	bar	bar	bar	mm	kg/m	m		m	
100.0	± 1.0	8.0	116.5 ± 1.5	6	15	0.9	450	4.30	20	0095016	■
									40	0096724	200
102.0	± 1.0	8.0	118.5 ± 1.5	6	15	0.9	500	4.38	15	5600616	200
									20	5600617	200
125.0	± 1.2	9.5	144.0 ± 1.5	6	15	0.9	550	6.30	20	0094152	120
									40	5009671	120
127.0	± 1.2	9.5	146.0 ± 1.5	6	15	0.9	550	6.39	15	5026098	120
									18	5026099	120
150.0	± 1.2	10.0	170.0 ± 1.5	6	15	0.9	650	7.77	20	5008847	120
									40	5600665	120
152.0	± 1.2	10.0	172.0 ± 1.5	6	15	0.9	650	7.87	15	5013908	120
									18	5013907	120
204.0	± 1.5	12.0	228.0 ± 2.5	6	15	0.9	1200	12.468	40	5008239	40

Branding

