


AIRWAP DIN

INDUSTRIAL MAINTENANCE
Compressed air applications

TRELLEBORG AIRWAP DIN



Applications

Air hose for pneumatic tools and any other compressed air applications
Also suitable (under certain conditions) for industrial water.

Advantages

- Good resistance to abrasion.
- Good flexibility.
- Good economical solution.

Technical description

Inner tube: SBR, black, smooth.

Reinforcement: synthetic yarns.

Cover: SBR, black, smooth.

Temperature range: - 30 °C to + 70 °C.

AIRWAP DIN

20/02/2007

ID	Wall thickness	OD	Working pressure	Bursting pressure	Bending radius	Weight	Length	Article number	Stock (■)		
mm	mm	mm	bar	bar	mm	kg/m	m				
6	± 0,5	3.00	12	± 0.7	20	60	18	0.16	20	5501258	■
									40	5501259	■
									80	5501260	■
8	± 0,6	3.00	14	± 0.7	20	60	25	0.19	120	5501261	■
									20	5501262	■
									40	5501263	■
10	± 0,7	3.50	17	± 0.8	20	60	35	0.26	80	5501264	■
									120	5501265	■
									20	5501266	■
13	± 0,6	4.50	22.5	± 0.7	20	60	60	0.40	40	5501267	■
									80	5501268	■
									120	5501269	■
16	± 0,7	5.60	27.6	± 0.8	20	60	70	0.61	20	5501325	■
									40	5501326	■
									80	5501327	■
19	± 0,8	5.60	30.6	± 1.1	20	60	80	0.69	20	5501328	■
									40	5501329	■
									80	5501330	■
25	± 1.0	6.5	38.0	± 1.1	20	60	100	1.01	20	5501270	■
									40	5501271	■
									80	5501272	■
25	± 1.0	6.5	38.0	± 1.1	20	60	100	1.01	20	5501518	■
									40	5501519	■
									80	5501520	■

Branding

TRELLEBORG AIRWAP DIN

WP 20 bar - BP 60 bar

